

ITA fork capacities depending on load centers

inch mm	Cross-section																	
	ITA 2						ITA 3						ITA 4					
	1.5x3.15 40x80	1.4x4 35x100	1.5x4 40x100	1.75x4 45x100	1.5x4.75 40x120	1.75x5 45x125	1.75x4 45x100	2x4 50x100	2x4.75 50x120	1.75x5 45x125	2x1.75 50x125	2.25x5.25 60x130	2x5.5 50x140	2x6 50x150	2.25x5.25 60x130	2.25x6 60x150	2.75x6 70x150	3x6 75x150
Capacity (lbs) at LC 24"	3,690	3,690	4,620	5,510	5,510	5,510	5,510	6,480	8,330	7,400	9,250	11,020	9,250	9,250	13,220	15,430	19,840	22,040
Capacity (kg) at LC 610 mm	1,677	1,677	2,100	2,500	2,500	2,500	2,500	2,940	3,780	3,360	4,200	5,000	4,200	4,200	6,000	7,000	9,000	10,000
Capacity (lbs) at LC 36"	2,480	2,480	3,110	3,710	3,710	3,710	3,740	4,370	5,630	4,990	6,250	7,460	6,250	6,250	8,960	10,450	13,470	14,990
Capacity (kg) at LC 920 mm	1,130	1,130	1,430	1,690	1,690	1,690	1,700	1,985	2,555	2,265	2,840	3,390	2,840	2,840	4,065	4,740	6,110	6,800
Capacity (lbs) at LC 48"	1,810	1,810	2,350	2,800	2,800	2,800	2,800	3,300	4,240	3,760	4,720	5,640	4,720	4,720	6,770	7,900	10,200	11,350
Capacity (kg) at LC 1220 mm	850	850	1,275	1,280	1,280	1,280	1,280	1,500	1,930	1,710	2,145	2,560	2,145	2,145	3,075	3,586	4,630	5,150

The illustrations only represent the basic principles and do not constitute a contractual entitlement. Technical information will not be updated automatically.