



# SmartFork<sup>®</sup> FrontCam

## View ahead the load

### Your benefits



Field of view extension  
ahead the load



Precise targeting



Safe loading process

### Integrated camera in the fork tip

- Tip thickness only 28 mm despite fully integrated components
- Lens with 0° tilt angle



FrontCam



### From the field



Monitor view in the cab shows the view in  
front of the load



# SmartFork<sup>®</sup> FrontCam

## Technical information

### Energy supply and data transfer



**Signal output:**  
SmartFork<sup>®</sup> monitor 7" or 10"

- Proven video standard
- Up to 4 camera images simultaneously
- Installation with RAM mount possible



**Signal transmission:**  
WiFi

- Interference resistant through 2,4 GHZ digital radio
- Up to 10 systems simultaneously applicable
- Energy saving mode: automatic deactivation at a standstill



**Data- and energy transfer:**  
Mast cable, spiral cable

- Permanent energy supply, connection to the electrical system

### Scope of supply

1 SmartFork<sup>®</sup> incl. camera

1 fork as counterpart

Assembly material and tools are not included in the scope of supply.

### More safety in combination with

- ✓ SmartFork<sup>®</sup> SideCam
- ✓ SmartFork<sup>®</sup> EasySecure
- ✓ SmartFork<sup>®</sup> Laser
- ✓ SmartFork<sup>®</sup> Flash
- ✓ LUXX FC frontend camera
- ✓ LUXX RC rear view camera