

# KOALA ImpactProtector

## Protect the load

- ▶ Best possible protection for your goods – no damage due to the inner heel radius of the fork
- ▶ Collision protection in the fork back: preservation of sensitive surfaces
- ▶ Noise reduction
- ▶ Quick mounting – immediately ready for use
- ▶ Two options:
  - KOALA „red“ with two height-adjustable, integrated velcro strips, suitable for long-term application
  - KOALA „black“ with four integrated round magnets, suitable for short-term alternating use. During non-use simple fixing to the lift truck
- ▶ Easy attachment on the lift truck (e.g. on the mast) when not in use



**KOALA-R:** Mounting with adhesive strap (Velcro)



**KOALA-R:** supplied with 2 velcro straps long and 2 velcro straps short



**KOALA-S:** Mounting by magnets at the backside



Attach to the lift truck when not in use

| Article No. | Description                                      | Dimensions (inches) | Technical characteristics   |
|-------------|--|---------------------|---|
| KOALA-R     | ImpactProtector red with adhesive strap (Velcro) | 18.5 x 4 x 1.2      | <b>Polyurethane red</b><br>Shore hardness standard DIN 53505: 60 Shore A<br>Operating temperature -58°F to +212°F |
| KOALA-S     | ImpactProtector black with 4 magnets             | 17 x 2.8 x 1.2      | <b>Polyurethane black</b><br>Shore hardness DIN 53505: 63 Shore A<br>Temperature range -58°F to +212°F            |

The illustrations only represent the basic principles and do not constitute a contractual entitlement.