

FoldingForks in patented DuoLoc design

| Capacity (kg/pair) / LC (mm) | Cross- section blade / back (mm) | Front section folded (mm) | Blade length L (mm) | Art.-No. | CG* un- folded (mm) | Weight (kg) | Art.-No. | CG* un- folded (mm) | Weight (kg) |
|---------------------------------------|---|------------------------------------|------------------------------|------------------|------------------------------|----------------|------------------|------------------------------|----------------|
| | | | | ISO 2A | | | ISO 2B | | |
| | | | 800 | KGA-SBO2A0800201 | 173 | 50.4 | KGA-SBO2B0800201 | 164 | 53.4 |
| | | | 900 | KGA-SBO2A0900201 | 206 | 53.6 | KGA-SBO2B0900201 | 196 | 56.5 |
| | | | 1,000 | KGA-SBO2A1000201 | 241 | 56.7 | KGA-SBO2B1000201 | 230 | 59.7 |
| 2,000 | 100x40 | | 1,100 | KGA-SBO2A1100201 | 278 | 59.9 | KGA-SBO2B1100201 | 266 | 62.8 |
| 500 | 100x50 | 150 | 1,200 | KGA-SBO2A1200201 | 316 | 63.0 | KGA-SBO2B1200201 | 303 | 65.9 |
| | | | 1,300 | KGA-SBO2A1300201 | 355 | 66.1 | KGA-SBO2B1300201 | 341 | 69.1 |
| | | | 1,400 | KGA-SBO2A1400201 | 395 | 69.3 | KGA-SBO2B1400201 | 380 | 72.2 |
| | | | 1,500 | KGA-SBO2A1500201 | 436 | 72.4 | KGA-SBO2B1500201 | 420 | 75.4 |
| | | | 1,600 | KGA-SBO2A1600201 | 478 | 75.5 | KGA-SBO2B1600201 | 461 | 78.5 |
| | | | | ISO 2A | | | ISO 2B | | |
| | | | 800 | KGA-SBO2A0800251 | 175 | 59.2 | KGA-SBO2B0800251 | 167 | 62.8 |
| | | | 900 | KGA-SBO2A0900251 | 209 | 63.0 | KGA-SBO2B0900251 | 199 | 66.5 |
| | | | 1,000 | KGA-SBO2A1000251 | 245 | 66.8 | KGA-SBO2B1000251 | 234 | 70.3 |
| 2,500 | 120x40 | | 1,100 | KGA-SBO2A1100251 | 282 | 70.6 | KGA-SBO2B1100251 | 270 | 74.1 |
| 500 | 120x50 | 150 | 1,200 | KGA-SBO2A1200251 | 321 | 74.3 | KGA-SBO2B1200251 | 307 | 77.8 |
| | | | 1,300 | KGA-SBO2A1300251 | 360 | 78.1 | KGA-SBO2B1300251 | 346 | 81.6 |
| | | | 1,400 | KGA-SBO2A1400251 | 401 | 81.8 | KGA-SBO2B1400251 | 385 | 85.4 |
| | | | 1,500 | KGA-SBO2A1500251 | 442 | 85.6 | KGA-SBO2B1500251 | 426 | 89.1 |
| | | | 1,600 | KGA-SBO2A1600251 | 484 | 89.4 | KGA-SBO2B1600251 | 467 | 92.9 |
| | | | | ISO 3A | | | ISO 3B | | |
| | | | 800 | KGA-SBO3A0800351 | 165 | 79.9 | KGA-SBO3B0800351 | 153 | 87.5 |
| | | | 900 | KGA-SBO3A0900351 | 196 | 84.5 | KGA-SBO3B0900351 | 182 | 92.1 |
| | | | 1,000 | KGA-SBO3A1000351 | 230 | 89.1 | KGA-SBO3B1000351 | 214 | 96.7 |
| 3,500 | 130x45 | | 1,100 | KGA-SBO3A1100351 | 265 | 93.7 | KGA-SBO3B1100351 | 247 | 101.3 |
| 500 | 130x60 | 181 | 1,200 | KGA-SBO3A1200351 | 301 | 98.2 | KGA-SBO3B1200351 | 282 | 105.9 |
| | | | 1,300 | KGA-SBO3A1300351 | 339 | 102.8 | KGA-SBO3B1300351 | 317 | 110.5 |
| | | | 1,400 | KGA-SBO3A1400351 | 377 | 107.4 | KGA-SBO3B1400351 | 354 | 115.1 |
| | | | 1,500 | KGA-SBO3A1500351 | 417 | 112.0 | KGA-SBO3B1500351 | 392 | 119.7 |
| | | | 1,600 | KGA-SBO3A1600351 | 458 | 116.6 | KGA-SBO3B1600351 | 431 | 124.3 |
| | | | | ISO 3A | | | ISO 3B | | |
| | | | 800 | KGA-SBO3A0800501 | 171 | 104.6 | KGA-SBO3B0800501 | 157 | 114.9 |
| | | | 900 | KGA-SBO3A0900501 | 202 | 110.5 | KGA-SBO3B0900501 | 186 | 120.8 |
| | | | 1,000 | KGA-SBO3A1000501 | 236 | 116.3 | KGA-SBO3B1000501 | 217 | 126.7 |
| 5,000 | 150x50 | | 1,100 | KGA-SBO3A1100501 | 271 | 122.2 | KGA-SBO3B1100501 | 250 | 132.5 |
| 500 | 150x70 | 181 | 1,200 | KGA-SBO3A1200501 | 307 | 128.1 | KGA-SBO3B1200501 | 285 | 138.4 |
| | | | 1,300 | KGA-SBO3A1300501 | 344 | 134.0 | KGA-SBO3B1300501 | 320 | 144.3 |
| | | | 1,400 | KGA-SBO3A1400501 | 383 | 139.9 | KGA-SBO3B1400501 | 357 | 150.2 |
| | | | 1,500 | KGA-SBO3A1500501 | 422 | 145.8 | KGA-SBO3B1500501 | 395 | 156.1 |
| | | | 1,600 | KGA-SBO3A1600501 | 463 | 151.7 | KGA-SBO3B1600501 | 433 | 162.0 |

Further models on demand!

*CG = center of gravity

The illustrations only represent the basic principles and do not constitute a contractual entitlement.
 Technical information will not be updated automatically.