

VETTER Forks standard imperial sizes

Dimensions	Tip	Upper hook	Capacity kg / pair (600 mm)	Capacity lbs/pair (24")	Blade length (mm / inch)							
					920 36	1070 42	1220 48	1370 54	1520 60	1830 72	2130 84	2440 96
50 x 50 2 x 2 2A	F	90 mm* 3.54 in*	1,910	4,200	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15
100 x 35 1.25 x 4 2A	V	90 mm 3.54 in	1,700	3,700	330 / 10	330 / 10	400 / 10	450 / 10	450 / 10	450 / 10	450 / 10	450 / 10
100 x 40 1.5 x 4 2A	V	90 mm 3.54 in	2,500	5,500	450 / 10	520 / 10	500 / 10	510 / 10	510 / 10	510 / 10	510 / 10	510 / 10
100 x 45 1.75 x 4 2A	V	90 mm 3.54 in	2,500	5,500	450 / 11	615 / 11	625 / 11	550 / 11	550 / 11	625 / 11	625 / 11	625 / 11
125 x 40 1.5 x 5 2A	V	110 mm 4.33 in	2,500	5,500	450 / 10	550 / 10	550 / 10	550 / 10	550 / 10	550 / 10	550 / 10	550 / 10
125 x 45 1.75 x 5 2A	V	110 mm 4.33 in	2,500	5,500	450 / 11	550 / 11	550 / 11	550 / 11	550 / 11	610 / 11	610 / 11	610 / 11
50 x 50 2 x 2 3A	F	120 mm* 4.72 in*	1,910	4,200	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15	450 / 15
125 x 45 1.75 x 5 3A	V	120 mm 4.72 in	3,600	7,900	450 / 11	550 / 11	550 / 11	550 / 11	550 / 11	610 / 11	610 / 11	610 / 11
125 x 50 2 x 5 3A	V	120 mm 4.72 in	4,500	9,900	450 / 12	550 / 12	550 / 12	550 / 12	550 / 12	650 / 12	650 / 12	650 / 12
150 x 50 2 x 6 3A	V	140 mm 5.51 in	5,000	11,000	450 / 12	550 / 12	650 / 12	650 / 12	650 / 12	650 / 12	650 / 12	650 / 12
150 x 50 2 x 6 4A	V	150 mm 5.91 in	5,700	12,600	450 / 12	550 / 12	650 / 12	650 / 12	650 / 12	650 / 12	650 / 12	650 / 12
150 x 60 2.25 x 6 4A	V	150 mm 5.91 in	8,200	18,000	450 / 13	550 / 13	650 / 13	650 / 13	650 / 13	650 / 13	650 / 13	650 / 13
150 x 65 2.5 x 6 4A	V	150 mm 5.91 in	9,600	21,100	450 / 13	550 / 13	650 / 13	650 / 13	650 / 13	650 / 13	650 / 13	650 / 13

Taper / tip

* with re-inforcement plate

The illustrations only represent the basic principles and do not constitute a contractual entitlement. Technical information will not be updated automatically.